



PO Box 129, Strathpine QLD 4500
Telephone: 07 3205 3844
Fax: 07 3205 6240
Email: sales@filterfab.com
ABN 65 005 247 647

Material Safety Data Sheet

Page 1 of 3

Issue date: 20 January 2016

Not classified as Hazardous according to criteria of Worksafe Australia

FLAKED WAX ORIGINAL MSDS

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Jax Wax Pty Ltd Trueshine Wax
A.C.N. 094 854 485
A.B.N. 90 094 854 485
2/59 Station Street
Officer VIC 3809
Tel: 61 3 5943 2422
Fax: 61 3 5943 2421
Mobile: 0407 377 410
Email: jaxwax@bigpond.com

Product Name: IRONING WAX
Manufacturer's Product Code: Not available
Use: Lubrication of industrial ironing machines
UN Number: None allocated
Proper Shipping Name: NONE ALLOCATED
Dangerous Goods Class: None allocated
Subsidiary risk: None allocated
Packing Group: None allocated
Hazchem Code: None allocated
Poison Schedule: None allocated

2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE NAME	Proportion	CAS Number
Waxy mixture	100%	Proprietary

All ingredients in this product are considered to be non-hazardous according to the criteria of Worksafe Australia.

3. HAZARD IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA.

HAZARD CATEGORY: None allocated

ACUTE HEALTH EFFECTS

Swallowed: None known. Product is edible
Eye: None known.
Skin: None known
Inhaled: Inhalation of droplets may cause pneumonitis
Chronic: None known

4. FIRST AID MEASURES

Swallowed:	No treatment normally required
Eye:	Irrigate with water for at least 15minutes. Seek medical advice
Skin:	Wash with soap and water
Inhaled:	Seek medical advice
First Aid Facilities:	Basic facilities required
Advice to Doctor:	Treat symptomatically

5. FIRE-FIGHTING MEASURES

Fire/Explosion Hazard

Slight if exposed to flame or very high temperatures. Incompatible with strong oxidizing agents. Burning will produce dense smoke, acid gases, acrolein.

Extinguishing Media: CO₂, BCF, dry powder, foam.

6. HANDLING AND STORAGE

Storage Precautions

Not Hazardous. Exposure to above ambient temperatures degrades product. Exposure to ultra violet light must be minimized to prevent oxidation.

Spills and Disposals

Spilt material is slippery and should be cleaned up immediately. Spilt material should be shovelled into disposal containers. Do not allow product to contaminate wastewater, drains or streams and other natural watercourses. Dispose in conformance with local waste disposal regulations.

7. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

No threshold limit value known.

Engineering controls

No special ventilation required. Product is slippery when spilt on floors. Use non skid surfaces where spills may occur.

Personal Protection Equipment

No specific protective clothing is required for product in its solid state.

Flammability

Non-flammable will only burn if heated over 300°C approx.

8. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Off white fine prill at ambient temperature.
Melting point:	58°C - 60°C
Boiling point:	Decomposes, increases rapidly over 330°C
Vapour Pressure:	Less than 0.1kPa@25°C
Specific Gravity:	0.91-0.93@20°C



PO Box 129, Strathpine QLD 4500
Telephone: 07 3205 3844
Fax: 07 3205 6240
Email: sales@filterfab.com
ABN 65 005 247 647

FlashPoint: >300°C
Flammability Limits: Not available
Solubility in Water: Soluble in hydrocarbons

Page 3 of 3

Issue Date: 20 January 2016

9. ECOLOGICAL INFORMATION

Biodegradable by micro-organisms if adequate oxygen is available.

10. OTHER INFORMATION

Contact Point

Technical Manager:
Tel: 61 3 5943 2422

Disclaimer

This MSDS summarises our best knowledge of the health and safety hazard information available on the product and the measures to be used to handle and use the product safely. Each user should read this MSDS and consider the information in connection with the way the product is intended to be handled or used.