



Filterfab Pty Ltd

ABN 65 005 247 647

PO Box 129, Strathpine, Qld, 4500 Australia.

telephone: (07) 3205 3844

facsimile: (07) 3205 6240

email: sales@filterfab.com

web: www.filterfab.com

Safety Data Sheet

Page 1 of 3 Issue date: 1st November 2019

Not classified as Hazardous according to criteria of Worksafe Australia

FILTERFAB FLAKED IRONING WAX

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Filterfab Pty Ltd

16 Leanne Crescent Lawnton Qld 4501

tel 07 3205 3844

Product Name: Flaked Original WAX

Manufacturer's Product Code:131FLK

Use: Lubrication of industrial ironing machines

UN Number: None allocated

Proper Shipping Name: NONE ALLOCATED

Dangerous Goods Class: None allocated

Subsidiary risk: None allocated

Packing Group: None allocated

Hazchem Code: None allocated

Poison Schedule: None allocated

2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE NAME Proportion CAS Number

Waxy mixture 100% Proprietary

All ingredients in this product are considered to be non-hazardous according to the criteria of

Worksafe Australia.

3. HAZARD IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO THE CRITERIA OF WORKSAFE AUSTRALIA.

HAZARD CATEGORY: None allocated

ACUTE HEALTH EFFECTS

Swallowed: None known. Product is edible

Eye: None known.

Skin: None known

Inhaled: Inhalation of droplets may cause pneumonitis

Chronic: None known

4. FIRST AID MEASURES

Swallowed: No treatment normally required

Eye: Irrigate with water for at least 15minutes. Seek medical advice

Skin: Wash with soap and water

Inhaled: Seek medical advice

First Aid Facilities: Basic facilities required

Advice to Doctor: Treat symptomatically

5. FIRE-FIGHTING MEASURES

Fire/Explosion Hazard

Slight if exposed to flame or very high temperatures. Incompatible with strong oxidizing

agents. Burning will produce dense smoke, acid gases, acrolein.

Extinguishing Media: CO₂, BCF, dry powder, foam.

6. HANDLING AND STORAGE

Storage Precautions

Not Hazardous. Exposure to above ambient temperatures degrades product.

Exposure to

ultra violet light must be minimized to prevent oxidation.

Spills and Disposals

Spilt material is slippery and should be cleaned up immediately. Spilt material should be

shovelled into disposal containers. Do not allow product to contaminate wastewater, drains or

streams and other natural watercourses. Dispose in conformance with local waste disposal

regulations.

7. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

No threshold limit value known.

Engineering controls

No special ventilation required. Product is slippery when spilt on floors. Use non skid

surfaces where spills may occur.

Personal Protection Equipment

No specific protective clothing is required for product in its solid state.

Flammability

Non-flammable will only burn if heated over 300°C approx.

8. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Off white fine prill at ambient temperature.

Melting point: 58°C - 60°C

Boiling point: Decomposes, increases rapidly over 330°C

Vapour Pressure: Less than 0.1kPa@25°C

Specific Gravity: 0.91-0.93@20°C

FlashPoint: >300°C

Flammability Limits: Not available

Solubility in Water: Soluble in hydrocarbons

9. ECOLOGICAL INFORMATION

Biodegradable by micro-organisms if adequate oxygen is available.

10. OTHER INFORMATION

Contact Point

Technical Manager:

Tel: 0419977721

Disclaimer

This MSDS summarises our best knowledge of the health and safety hazard information

available on the product and the measures to be used to handle and use the product safely.

Each user should read this MSDS and consider the information in connection with the way

the product is intended to be handled or used.